



BE 5528+ 4x2 (BS-VI)

BLUE ENERGY
MOTORS

1	Engine	Model	FPT N67 NG BSVI
		Capacity (L)	6.7
		Cylinders	6
		Max Power (HP)	280 HP @ 2200 rpm
		Max Torque (Nm)	1000 Nm @ 1200-1900 rpm
		ATS	3 Way Catalyst with CPF
2	Transmission	Type	Mechanical With Cable Shift
		No. of Gears / Speeds	9+1R
		Clutch type	Single Plate - Dry - Organic
		Clutch Diameter (mm)	395
3	Axle	Type	Single, Hub Reduction Axle, FDR 5.26
4	Tyre		295/90 R20 Radial Tube in Front & Rear (Dual)
5	Performance	Max Gradeability	25.19%
		Max governed speed (Kmph)	80 Kmph
6	Turning Circle Diameter (m)		15.1
7	Tractor Clearance Circle Diameter (m)		16.9
8	Frame (mm)		276 x 77 x 7
9	Suspension	Front	Parabolic
		Rear	Semi-Elliptical
10	Brakes	Front drum dia. (mm)	410 x 180
		Rear drum dia. (mm)	410 x 220
11	Fuel tank LNG	Capacity in litres	990 Litres single tank
		Empty Weight (kg)	498
		Material	Metal - Stainless Steel (Vacuum)
12	Battery	Capacity (Ah)	120
		Voltage (V)	24 (2x12)
13	Dimensions (mm)	Wheelbase	4200
		Overall Length	6550
		Overall Width	2550
		Overall Height	3015
		Ground Clearance	313
14	Weight	GCW (Ton)	55
		Kerb Weight (kg)	7117
15	Cabin	Type	4-point suspended, Tilttable, Fully air-conditioned with Sleeper berth
		Internal Dimensions (LXWXH) (mm)	2050 X 1680 X 1480
		Berth Dimensions (LXWXH) (mm)	2050 X 520 X 80
16	Features	Cabin AC	✓
		Telematics	✓
		LED Tail Lamps	✓
		Tilt and Telescopic Steering	✓
		Hyd. Power Assisted Steering	✓
		Energy Saving Compressor	✓



Note: In view of our policy of continuously improving our products, we reserve the right to alter specification or design without prior notice and without liability. Illustrations do not necessarily show the vehicle in its standard form. Accessories shown are not part of the standard equipment. Colour shades shown may vary. E. & O.E.

BLUE ENERGY COMMERCIAL VEHICLES PRIVATE LIMITED

Address: Gat No. 780, Opp. Mahindra vehicle Mfg. Plant, Nighoje Kurali Road Village, Nighoje, Chakan, Pune, Maharashtra, 410501

Email: info@blueenergymotors.com

Website: www.blueenergymotors.com